





REVISION HISTORY

DATE	REV.	DESCRIPTION	BY
25.05.2016	A	First release	rd_lto
19.08.2016	B		rd_lto
10.01.2018	C		rd_lto
15.04.2019	D		rd_lto



Direct fixture to fixture connection allows up to 0,5 m. center to center pitch.

General Technical Specification apply to this item

© 2019 HARMAN Professional Denmark ApS PROPRIETARY AND CONFIDENTIAL PROPERTY OF HARMAN. DO NOT DISCLOSE, REPRODUCE, OR PUBLISH WITHOUT WRITTEN HARMAN APPROVAL. ROHS RESTRICTION OF HAZARDOUS SUBSTANCES ALL MATERIALS USED IN THIS PART MUST BE ROHS COMPLIANT. SUPPLIER SHALL PROVIDE A CERTIFICATE OF ROHS COMPLIANCE WITH THE FIRST ARTICLE.	Material	FIRST ANGLE PROJECTION		HARMAN Professional Denmark ApS Oluf Palmes Allé 44 DK 8200 Aarhus N
	General linear tolerance			
	General angular tolerance	Color Grey	TITLE EXTERIOR DOT-HP, OPAL DOME FRONT W/ FLANGE BRACKET	
	General geometrical tolerance	Project number	NO. REV	
DIMENSIONS SHOWN ARE FOR REFERENCE AND INSPECTION ONLY. REFER TO CAD MODEL PROVIDED WITH THIS DRAWING FOR OVERALL DEFINITION OF PART GEOMETRY.		SIZE A3	SCALE 1:2	UNIT mm
		DO NOT SCALE DRAWING	SHEET 1	OF 1